



Go **green** and reduce waste !

Reduce your packaging costs

Save on cardboard disposal costs

LOW cost

LOW maintenance

Safe and user friendly

No precutting required

Perfect for void fill

Small footprint

Dust extraction outlet built in



Turn unwanted cartons



Into soft, flexible material



And save on packaging.



	CP 320 S2	CP 323 S2	CP 422 S2	CP 428 S2	CP 430 S2
Loading Width (cardboard size)	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Cutting Width (output width)	320 mm	320 mm	420 mm	420 mm	420 mm
Cardboard Thickness	12 mm	15 mm	18 mm	20 mm	20 mm
Production rate (output)	2 – 3 m3/hr	3 – 4 m3/hr	4 – 6 m3/hr	6 – 9 m3/hr	7 – 10 m3/hr
Throughput Rate	12 m/min	12m/min	13 m/min	14 m/min	16 m/min
Motor Size	1.1 kW	1.5 kW	1.8 kW	3.0 kW	4.0 kW
Voltage	240 V	415 V	415 V	415 V	415 V
Dimensions H x W x D (mm)	980 x 660 x 660	980 x 660 x 660	980 x 660 x 660	1100 x 750 x 800	1100 x 750 x 800
Weight (kgs)	110	115	125	252	295

